

Network Working Group  
Request for Comments: 145  
NIC: 6739  
Updates: 123  
Obsoletes: 127

J. Postel  
UCLA - NMC  
4 May 1971

### Initial Connection Protocol Control Commands

The following is my interpretation of the exchange between NCP's which would be necessary to carry out the Initial Connection Protocol of RFC #123. (This note corrects an error pointed out by Eric Harslem of RAND).

Server NCP	User NCP
Listen for Connection L	RTS, U, L, l A
STR, L, U, 32	ALL, l , 1, 32 A
Send 32 bits of data in l message on link l A	
(value is S)	Receive 32 bits of data from link l (value is S) A
CLS, L, U	CLS, U, L
STR, S+1, U+1, B s	STR, U+1, S, B u
RTS, S, U+1, l B	RTS, U, S+1, l C
wait for connection ALL, l , m , b B B B	wait for connection ALL, l , m , b C C C
data sent to link l C	data sent on link l B
data received on link B	data received on link l C

$l_A$ ,  $l_B$ , and  $l_C$  are links,  $m_A$  and  $m_B$  are messages allocations,  $b_A$  and  $b_B$  are bit allocations, and all other symbols are defined in RFC #123.

[This RFC is also available in .PS and. PDF format.]

[ This RFC was put into machine readable form for entry ]  
[ into the online RFC archives by Lorrie Shiota]