

# BSD 00, 000, 000 0000

## Abstract

00000000 00000000 0000 "00000000 00000000" 0000 000 00000000 00 0000 0000 0000 000000 0000000000'0  
00000000 000000000 00000000 0000 0000000000 000000000 00000000 00000000 00000000 0000 00 00000000 00000000  
000000000000 0000 000000 00000000 00.0% 00000000000 00000000 0000 00 0000000000 00 00.0% 00000000000 00000000  
00 BSD 000000000 00000000 00000000000; 0000000000 00000000 0000000000000000 0000000, 00000, [Yahoo!](#) BSD 00000000  
00000000 0000 0000000 000000000 FTP 00000000 [ftp.cdrom.com](#) BSD 00000000 0000 0000000000 000000 0.0  
000000000 0000 00000 0000000 0000 00000000 BSD'0 000000 00 00000000 0000, 0000 0000 00000000 0000 BSD 0000  
0000000000 0000000 00000 00000000

BSD'0 000000000 0000000 000000 00 0000 000000 0000 ? 00 000000000 0000 00000 0000 00000 00000000000000 00 000000  
000000000000

00 0000000000 BSD 0 00000000000 00 0000000000000000 000000 00000000 0000 00000

## Table of Contents

1. BSD 00 ? .....	1
2. 000 0000000!!! 0000 0000 00 ? .....	2
3. BSD 000 00000000 00 ? .....	3
4. BSD 0000 0000000000 .....	3

## 1. BSD 00 ?

BSD 0000 00 *Berkley Software Distribution* 0 000000000000 BSD 0000 0000000000000000 000000000000000,  
00000000 0000 000000000 00000000000 0000000 0000 AT&T'0 000000000000 00000000 000000000 0000 00000000  
0000 00 000000000 0000 00000000 4.4BSD-Lite 0000 00000000 00 0000000000 00000000 0000 0000 00000000 0000000000  
0000000000 000000000 0000 00000000 00 00000000000000 0000 00000 0000000000 0000000000 00000000 00000000  
0000, 0000 000000 000000000000 00 00000 (GNU) 00000000000 0000000000000000 0000 BSD 0000000000 0000000000 00000000  
00000000 00 0

### BSD 00000000

0000 000000000 0000000000 000000 0000 0 000000 000000 0000 0000 0000000 0000000 000000 0000000000 000000  
000000 00000000 000000000000 00000000000 00000

00000000 00000000 00, 00000000000 00000000 0000 00000 00000000000 0000000, 0000000 BSD 00000000000 0000000  
00000000 0000 00000 00000000000 000000 000000000000000 0000 0000000000 000000000000 0000

### C 0000000000

0000 00 0000000000 00000000000 API 000000000 0000 0000000000

BSD C 000000000000 0000000000 0000000000 0000000000 0000, 00000 (GNU) 000000000000 0000 00000 0000





BSD'의 주요 구성 요소는 다음과 같습니다.

## 4.2. BSD 프로젝트의 구조

BSD 프로젝트는 여러 하위 프로젝트로 구성되어 있으며, 각 프로젝트는 CVS로 관리됩니다. BSD 프로젝트의 구조는 다음과 같습니다.

BSD 프로젝트의 구조는 다음과 같습니다.

각 프로젝트는 BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다.

### 조직

BSD 프로젝트는 여러 하위 프로젝트로 구성되어 있으며, 각 프로젝트는 CVS로 관리됩니다.

BSD 프로젝트의 구조는 다음과 같습니다. BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다. (Principal Architect) 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다. "Backing Out" BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다.

### Core Team의 역할

FreeBSD와 NetBSD는 BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다.

BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다.

1. BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다. (Chief Architect) 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다.
2. BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다.
3. BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다. BSD 프로젝트의 주요 구성 요소인 BSD 프로젝트의 구조를 형성합니다.



BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X

- 4.4 BSD license and other licenses are used in BSD/OS and Mac OS X, and FreeBSD's BSD/OS license is also used
- BSD license and other licenses are used in Mac OS X and FreeBSD's BSD license is also used

### 4.4. BSD and GNU licenses

BSD license and GNU General Public License (GPL) are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

### 4.5. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

### 4.6. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to anyone who receives the binary code.

- 00000000000 00000000 BSD'00 0000000 000000 0000 00000000 000000 0000 00 0000 0000000000 0000000000 0000000000 00000000 00000000 BSD'0 00000000000 00000000 00000000000 0000000 0000000

## 4.7. BSD 000000000000 000000 0 0000000000000

BSDi 00000000 BSD/OS 00000000000 00000 00000 00000000 0000000000 00000 FreeBSD 0000000000 00000 00000000 0000000000

00000000 FreeBSD, NetBSD 0 OpenBSD'0 00000000000 0000000000 000000 0000000 000000000000 0000000000 000000000000 00000000000 00000 000000 000000 00000